

## Silver Plated Copper Flat Braids

**Specifications:** Braided with a specific number of ends of tinned copper wire per ASTM-B-298, to the construction below, then mill-rolled to the specified width and thickness.

HP Part Number	AA59569A	Nominal Flat Width	Construction	AWG Equivalent	Nom CMA	Nom Amps*
7223	F36S0031	3/64"	24-1-36	22	600	7
7225	F36S0062	3/32"	24-2-36	19	1200	11
7229	F36S0078	1/8"	24-3-36	18	1800	16
7229/1	F36S0109	5/32"	24-4-36	16	2400	19
7230	F36S0125	3/16"	24-5-36	15	3000	25
7231	F36S0171	1/4"	24-7-36	14	4200	32
7231/1	F36S0156	1/4"	24-10-36	12	6000	40
7231/2	F36S0203	9/32"	24-13-36	11	7800	46
7233	F36S0375	5/8"	48-8-36	10	9600	53
7233/1	F36S0500	5/8"	48-11-36	9	13200	62
7234	F36S0781	3/4"	48-18-36	7	21600	85
7240	F30S0437	1/2"	24-10-30	6	24000	93
7242	F30S0500	5/8"	24-15-30	5	36000	120
7262	F30S0875	1 3/8"	48-7-30	5	33600	100
7268	F30S1375	1 1/2"	48-11-30	3	52800	145