

## Tinned Copper Tubular Braids

HP Part Number	AA59569A	Nominal Flat Width	Construction	AWG Equivalent	Nom CMA	Nom Amps*
6110	R32T0062	1/16"	16-1-32	20	1024	9
6112	R32T0109	7/64"	16-2-32	17	2048	18
6114	R32T0125	1/8"	24-2-32	15	3072	25
6116	R32T0171	11/64"	24-3-32	14	4608	32
6118	R32T0203	13/64"	24-5-32	11	7680	46
6120	R32T0375	3/8"	48-3-32	11	9216	46
6122	R32T0500	1/2"	48-4-32	9	12288	62
6124	R32T0781	25/32"	48-7-32	7	21504	88
6132	R34T0062	1/16"	16-2-34	19	1270.4	11
6134	R34T0109	7/64"	16-4-34	16	2540.8	19
6136	R34T0125	1/8"	24-3-34	16	2858.4	19
6137	-	9/64"	24-4-34	15	3811.2	26
6138	R34T0171	11/64"	24-5-34	14	4764	32
6140	-	3/16"	24-6-34	13	5716.8	38
6142	-	1/4"	24-7-34	12	6669.6	41
6144	-	3/8"	24-8-34	11	7622.4	46
6145	R34T0375	3/8"	48-5-34	10	9528	53
6146	R34T0500	1/2"	48-7-34	9	13339.2	62
6148	-	5/8"	48-8-34	8	15244.8	64
6150	-	11/16"	48-10-34	7	19056	81
6152	R34T0781	25/32"	48-11-34	7	20961.6	85
6153	-	13/16"	48-12-34	7	22867.2	90
6160	R36T0031	1/32"	24-1-36	22	600	7
6162	R36T0062	1/16"	24-2-36	19	1200	11
6163	R36T0078	5/64"	24-3-36	18	1800	16
6164	R36T0109	7/64"	24-4-36	16	2400	19
6166	R36T0125	1/8"	24-5-36	15	3000	25
6167	R36T0156	5/32"	24-10-36	12	6000	40
6168	R36T0171	11/64"	24-7-36	14	4200	32
6170	R34T0203	13/64"	24-8-34	11	7622.4	46
6170/1	R36T0203	13/64"	24-13-36	11	7800	46
6171	R36T0250	1/4"	24-16-36	10	9600	53
6171/1	R30T0281	9/32"	24-5-30	9	12000	60
6171/2	R30T0375	3/8"	24-7-30	8	16800	75
6172	R36T0375	3/8"	48-8-36	10	9600	53
6173	R30T0437	7/16"	24-10-30	6	24000	90
6173/1	R30T0500	1/2"	24-15-30	5	36000	120
6174	R36T0500	1/2"	48-11-36	9	13200	62
6175	R30T0562	9/16"	48-10-30	3	48000	145
6175/1	R30T0656	21/32"	48-16-30	1	76800	190
6176	R36T0781	25/32"	48-18-36	7	21600	88
6176/1	-	7/8"	48-19-36	7	22800	93
6177	R30T0875	7/8"	48-7-30	5	33600	100
6178	R30T1000	1"	48-8-30	4	38400	120
6179	R30T1125	1 1/8"	48-9-30	4	43200	130
6180	R30T1250	1 1/4"	48-10-30	3	48000	145
6181	R30T1375	1 3/8"	48-11-30	3	52800	145
6182	R30T1500	1 1/2"	48-12-30	3	57600	145
6183	R30T2000	2"	48-14-30	2	67200	180
6184	-	2 1/4"	48-16-30	1	76800	190

### Specifications

Braided with a specific number of ends of tinned copper wire per ASTM-B-33, to the construction below, then mill-rolled to the specified width and thickness.